



BETRA

BEIRUT ELECTRO TRADE

Product Catalogue

Electrical safety equipment, circuit protection, enclosures, cable management, earthing and professional tools.

Sole distributor in Lebanon of Sofamel electrical safety products

10

BRANDS

140

PRODUCTS

48

CATEGORIES

Habib Lteif, Forn El Chebbak, Lebanon

sales@betraonline.com · 01 293 002 / 01 293 005 · WhatsApp +961 76 896 316

betraonline.com

Contents

Sofamel	Electrical safety & tools · 45 products
Lumel	Measurement & control · 6 products
DF Electric	Fuses & fuse holders · 18 products
KSS	Cable management · 13 products
Iskra	Circuit protection · 15 products
Tempa Pano	Enclosures & accessories · 11 products
Plastim	Enclosures & climate control · 8 products
Gemini	Earthing & grounding · 3 products
4C Electric	Cable accessories · 1 products
GLOW	Lighting · 20 products



ELECTRICAL SAFETY & TOOLS

Sofamel

Sole distributor in Lebanon of Sofamel electrical safety products: insulating gloves, dielectric boots and mats, voltage detectors and measurement instruments. We also stock the Sofamel cable lug, connector and professional tool ranges.

45 products · 16 categories



30201 SG

Dielectric gloves

The natural latex base provides excellent dielectric properties. The greater the glove thickness, the higher its electrical resistance. The ergonomic design enhances comfort, offering superior softness and...

Average tensile strength ≥ 16 MPa

Average elongation at break $\geq 600\%$

Puncture resistance ≥ 18 N/mm

Tension set $\leq 15\%$

530110 530120 530150 530160
530190 530200 530230 530240
530270 530280



30202 SGM

Composite insulated gloves

Composite insulating gloves provide electrical, mechanical, and arc-flash protection; therefore, it is not necessary to use them in combination with a separate mechanical protective over-glove. The Composite...

Protection **Electrical / Mechanical / Arc-flash**

Average tensile strength ≥ 16 MPa

Average elongation at break $\geq 600\%$

Tension set $\leq 15\%$

531120 531150 531160 531190
531200 531230 531240 531270
531280 531310



30201 SGC COMFORT

Ultra-thin insulating gloves

Ultra-thin, high-sensitivity insulating glove (Class 0) The new SGC Comfort glove combines exceptional tactile sensitivity with full Class 0 electrical protection, while also maintaining excellent mechanical...

Abrasion **2**

Cut (blade) **1**

Tear **2**

Puncture **1**

Dielectric Boots & Overboots



30601 DB2

Dielectric boots / CLASS 2

Each boot tested to 20 kV (AC testing as standard, DC testing available on request). Leakage current less than 5 mA at 5 kV and less than 18 mA at 20 kV. Meets the requirements of ASTM F1117 (20 kV) and ASTM...

715160 715165



30602 OB2

Dielectric compact overboots / CLASS 2

Single-piece injection-moulded construction with integral moulded fastener ensures no seams or mounting/fastener holes that could cause leakage. No metal fasteners or components are used in the construction....



30602 OB3

Dielectric HV3 maxi overboots / CLASS 3

Ingenious rear-entry design ensures the boot is quick and easy to put on and take off. Ideal for personnel who must continually enter and exit high-voltage areas. Lightweight. Fluorescent green color. Seamless...

Insulating Mats

SOFAMEL



30502 AD

Insulating mat

Resistance to abrasión: 182 mm 3
Chemical resistance: Acids and Bases diluted - Moderate Acids and Bases Concentrates - Not recommended
Hydrocarbon - Not recommended Organic solvents - Not recommended...

Specific Rubber Base **natural rubber SBR**

Specific weight **1.51 g/cm 3 (specific gravity)**

Hardness **71**

Shore A Tensile Strength **75.5 kg/cm 2**

585180	585181	585182	585183
585184	585185	585186	585200
585210	585220		

Voltage Detectors

SOFAMEL



31006 D-TUERI PRO 7.9/69 kV

Personal voltage detector - Medium & High voltage- Optical...


Omni-directional personal electric field detector. Additional individual safety device designed for personnel working in areas with electrical voltage, such as inspection tasks, cleaning operations,...

Utilization range **Between 7.9-69 kV**

Operating frequency **50 and 60 Hz**

Degree of protection **IP 65**

Luminous power **2 W**



31003 POWER LIGHT

Electronic voltage detector - Medium Voltage - Optical &...

VOLTAGE RANGES from 1 to 5 kV or from 5 to 79 kV Lamp in the top part with high-brightness, low-consumption LEDs, for use in dark places. Lamp use is independent of the detection system. Voltage present...

Working temperature range **-25°C to +55°C**

Manufactured according to **2003+A1:2009 and**

UNE-EN 61243-1 **2006+A1:2011 standards (except voltage...**

645280	645285
--------	--------



31009 Destornillador buscafases

Voltage tester screwdriver. Phase-testing screwdriver for detecting voltage up to 500 V.



31009 CTL-1000
Professional multimeter CTL-1000 with True RMS - Optical &...

Digital AC/DC, T-RMS clamp meter with automatic and manual ranges and a VFD frequency converter. The CTL-1000 has a large 13 mm HD display with 6000 digits and a backlight for easy reading. It has functions...

DC voltage	6 V / 60 V / 600 V / 1000 V
AC voltage	6 V / 60 V / 600 V / 1000 V
Alternating Current	60 A / 600 A / 1000 A
Direct Current	60 A / 600 A / 1000 A

635360



31009 CIT-10

Digital insulation tester - Digital

It is used to measure the quality of electrical insulation in cables, motors, transformers, etc., both in new installations and during maintenance, for basic and specialized categories. It also detects direct...

Display	LCD with backlight
Resistance Range	0.01 MΩ – 10.00 GΩ
Insulation Tests	50 V, 100 V, 250 V, 500 V and 1000 V
Power supply	6 x 1.5 V AA batteries



30909 ERLAIN

Potential drop

Earthing equipment for overhead lines, easy to use for only one operator that besides facilitates the verification of absence of tension with a voltage detector (not included). Thanks to the operation sections...

Note	the maximum tightening torque for the...
------	--

660400 660405

**10403 TDC/S****Bimetallic cable lug**

TDC/S bimetallic cable lug are manufactured from aluminum alloy bar (purity $\geq 99.5\%$), entirely tinned via electrolytic bath. Neutral grease is applied internally to prevent oxidation. Designed for underground...

111090	111100	111110	111118
--------	--------	--------	--------

111119	111120	111130	111139
--------	--------	--------	--------

111140	111150
--------	--------

**10104 T90°****Copper cable lug 90°**

T90° cable lug manufactured from electrolytic copper tubing with a tin-plated surface finish to electrical contact. Its particular orientation makes it suitable for installations where connection needs a...

008270	008280	008290	008320
--------	--------	--------	--------

008330	008370	008380	008420
--------	--------	--------	--------

008430	008520
--------	--------

**10101 T****Copper cable lug**

T terminals are made of high-conductivity electrolytic copper tube, with a tinned surface finish to improve electrical contact. They feature an inspection hole that allows easy verification of correct...

010100	010110	010120	010130
--------	--------	--------	--------

010140	010150	010160	010170
--------	--------	--------	--------

010180	010190
--------	--------

**10110 M****Copper butt-connector**

M copper butt-connector manufactured from electrolytic copper tubing with a tin-plated surface finish to improve electrical contact. Incorporates a central stop which facilitates the correct cable positioning....

015100	015110	015120	015130
--------	--------	--------	--------

015140	015150	015160	015170
--------	--------	--------	--------

015190	015200
--------	--------


**10113 TCD****DIN 46235 copper cable lug**

TCD copper cable lugs are manufactured from electrolytic copper with a tin-plated finish to protect against oxidation. Their reinforced design makes them particularly suitable for installations exposed to...

005270	005280	005320	005330
--------	--------	--------	--------


005370	005380	005420	005430
--------	--------	--------	--------

005520	005530
--------	--------

**APF****Cord end terminal**

APF cord end terminal manufactured from electrolytic copper capillary tube with a tinplated finish to improve electrical contact. The insulating part is made of nylon (PA). They feature an "Easy Enter" design,...

245100	245110	245120	245130
245140	245150	245160	245170
245180	245190		

**APF/D****Twin cord end terminal**

APF/D cord end terminal manufactured from electrolytic copper capillary tube with a tinplated finish to improve electrical contact. The insulating part is made of nylon (PA). They are designed for electrical...


255100	258110	255120	255130
258140	258150	258160	258170
258180	256100		

Insulated Terminals

**11001 AT****Insulated ring terminal**


AT terminals are made of tinned electrolytic copper, insulated with flame-retardant PVC. Color-coded according to DIN 46237. UL certified.

270100	270110	270120	270130
270140	270160	270170	270180
270190	270200		

**11002 AU****Insulated fork terminal**

Ideal for quick screw connections without full removal. Made of tinned electrolytic copper with flame-retardant PVC insulation. Color-coded per DIN 46237. UL certified.

275100	275110	275120	275130
275140	275160	275170	275180
275190	275200		

**11003 AFH****Insulated female connector**


Faston-type female terminals for quick, secure connections. Made of tinned electrolytic copper with PVC insulation and internal metal sleeve for vibration resistance. Color-coded per DIN 46237.

280100	280120	280130	280140
280150	280160	280170	

**11003 AFH/A****Fully insulated female connector**

AFH/A connector manufactured from electrolytic copper strap with PVC insulation. Incorporates an inside fitting which provides better security to stand possible mechanical vibrations.

305100	305110	305120
--------	--------	--------




11401 SCF/C

MC4 type connectors for 1000 V and 1500 V

MC4-type connectors, male and female, ensure a reliable connection and watertight sealing between cable terminations and the various components of a photovoltaic installation. SCF/C-1000V for cross-sections of...

501020



11402 SCF/FUSE

MC4 Type fuse holder for 1000 V and 1500 V

Integrated, watertight 20 A fuse in MC4 connector. Possibility of changing fuse (from 15/20 A). SCF/FUSE-1000V female-male SCF/FUSE-1500V female-male


501044

501045

501046


501047

Cable Cutters




380 SF-21

For copper and aluminum cables up to 16 mm².




380 SF-30

For copper and aluminum cables up to 35 mm².



380 SF-31


For copper and aluminum cables up to 55 mm².



380 SF-20


For copper and aluminum cables up to Ø 38 mm.

Crimping Tools For Non Insulated Terminals




385 SF-7

For copper terminals and thin-wall tubular aluminum from 10 to 95 mm². Section adjustment by screw.




385 SF-17

For tubular copper terminals from 6 to 50 mm². Section adjustment by revolver system. Hexagonal compression.



385 SF-37

For tubular copper terminals from 6 to 120 mm². Section adjustment by revolver system. Hexagonal compression.



385 SF-8

For cable lugs from 1.5 to 16 mm². Punching compression.

Crimping Tools For Cord End Terminals

SOFAMEL



390 SF-42

For cord end terminals from 0.5 to 6 mm².
Compression system by squared diaphragm.



390 SF-9

For cord end terminals from 0.5 to 2.5 mm².
Compression system by spring.



390 SF-6

For cord end terminals from 0.5 to 16 mm².
Compression system by spring.



390 SF-10

For cord end terminals from 0.75 to 10 mm². Compression using ratchet mechanism.



390 SF-35

For cord end terminals from 16 to 35 mm².
Compression using ratchet mechanism.

Crimping Tools For Insulated Terminals

SOFAMEL



395 SF-16

For insulated terminals from 1.5 to 6 mm².
Compression using ratchet mechanism.



MC4 Type Fuse Holder

MC4 type fuse holder for 1500V .
Integrated, watertight 20 A fuse in MC4 connector. Fuse dimensions: 10x85 mm.
Possibility of changing fuse (from 10 A to 50 A)



20104 SF-6J

Crimping tools for insulated terminals

For insulated terminals from 0.5 to 6 mm².
Compression using ratchet mechanism.

Crimping Tools For Solar Connectors

SOFAMEL



385 SF-MC4

Crimping tool for solar connectors to 2.5-6 mm² cables for photovoltaic installations.



20105 EPM-52

Tool for stripping primary insulation

Suitable for stripping the primary insulation layer of medium voltage cables. Offers precise adjustment of the cutting angle and an efficient stripping speed, adapting to different requirements. Can also be...

Stripping speed	adjustable in 6 levels, for optimal...
-----------------	--



20202 EBC-13C

Electrohydraulic tools

Battery-powered hydraulic crimping tool C-shaped head that rotates 180 degrees. 2-speed hydraulic system. Independently designed oil return system can safety react without electricity. The trigger switch and...

Copper	up to 400 mm²
Aluminium	up to 300 mm²
Bimetallic	up to 240mm²

412001



LUMEL

MEASUREMENT & CONTROL

Lumel

Current transformers for power measurement, plus time and protection relays for monitoring and control.

6 products · 2 categories

Current Transformers

LUMEL



LCTB 50/62/74/86

Compact and accurate current transformers for efficient power measurement.



LCTB 100

Durable current transformer designed for precise electrical measurements.



LCTB 140

Reliable transformer for high-performance current monitoring.



LCTS 93/125/155

Flexible and easy-to-install transformers for diverse electrical setups.

Time and Protection Relays Control

LUMEL



LTR10

A versatile time relay for precise and adjustable time control in electrical circuits.



LP10-V

A reliable protection relay designed to monitor and safeguard electrical systems against voltage fluctuations.



FUSES & FUSE HOLDERS

DF Electric

Cylindrical and NH knife-blade fuse links, photovoltaic gPV ranges up to 1500V DC, fuse holders and control transformers.

18 products · 5 categories

**10x38 gPV Cylindrical Fuse Link**

Voltage (U) **1000V DC Current
(I_n): 1A...20A**

Breaking Capacity **30kA**

**14x51 gPV Cylindrical Fuse Link**

Voltage (U) **1100V DC / 1000V DC
Current (I_n): 15A |...**

Breaking Capacity **10kA / 30kA**

**10x85 gPV Cylindrical Fuse Link**

Voltage (U) **1500V DC / 1200V DC
Current (I_n):...**

Breaking Capacity **30kA / 10kA**

**10/14x85 gPV Cylindrical Fuse Link**

Voltage (U) **1500V DC Current
(I_n): 20A...32A**

Breaking Capacity **30kA**

**22x65 Cylindrical gPV Fuse Link**

Voltage (U) **1500V DC Current
(I_n): 40A...60A**

Breaking Capacity **30kA**

NH Knife-Blade

**NH000**

Compact NH fuse-link with a current rating typically ranging from 2A to 100A. Ideal for low-voltage electrical systems such as small distribution boards or control panels. Protects short circuits and overloads in compact installations.

**NH00**

Standard NH fuse-link with current ratings typically up to 160A. Suitable for industrial and residential electrical systems. Ensures consistent overcurrent protection while adhering to IEC 60269 standards.

**NHC1**

Heavy-duty NH fuse-link designed for demanding environments. Offers higher breaking capacity, suitable for industrial machinery or power distribution networks. Provides reliable protection for circuits operating under high load conditions.

**NH1**

Medium-sized NH fuse-link with current ratings generally up to 250A. Used in medium-capacity installations such as transformer protection or motor circuits. Ensures fast response to short circuits and overloads for enhanced safety.

**NHC2**

High-capacity NH fuse-link with ratings typically up to 400A. Ideal for high-demand circuits such as heavy-duty industrial equipment or large power systems. Built for durability and efficient fault current interruption.

**NH2**

Large NH fuse-link with ratings generally up to 630A. Designed for critical electrical systems like substations or large industrial plants. Provides maximum reliability for safeguarding high-power installations.



NH00 Screw

A screw-terminal fuse base designed for NH00 fuse-links. Ensures secure and stable mounting of fuses in electrical panels. Manufactured for high mechanical and thermal durability, ensuring long-lasting performance.

Transformers

DF ELECTRIC



TR21

A compact and versatile control transformer designed for industrial and automation systems. Converts high input voltage to lower output voltage to power control circuits and devices. Features easy-to-use screw terminals and a robust metal frame for...



TR28 2.2

An advanced power transformer with a high output capacity, suitable for demanding applications. Offers precise voltage regulation and protection for sensitive electrical equipment. Enclosed in a protective housing for enhanced safety and long-term...

PMX Cylindrical Fuse Holders

DF ELECTRIC



10x38 PMX PV fuse holder

Voltage (U)	1000V DC Current
	(I_n): 32A



14x51 PMX PV fuse holder

Voltage (U)	1100V DC Current
	(I_n): 50A



22x65 PMX PV fuse holder

Voltage (U)	1500V DC Current
	(I_n): 100A

PML Cylindrical Fuse Holders

DF ELECTRIC



PMLe 10/14x85 PV fuse holder

Size	10x85 10/14x85
	Voltage (U_n): 1500V DC...
Poles	1P



CABLE MANAGEMENT

KSS

Wiring ducts, cable markers, nylon cable ties, glands, conduits, wire connectors and identification accessories.

13 products · 8 categories

Wiring Ducts

KSS



Wiring Duct Slotted

HVD Series Material	High impact, warp-proof PVC,...
SLOT	4mm



Round Type Wiring Duct

Material	High impact, warp-proof PVC,...
Color	Grey
Width	70mm / 90mm

Cable Markers

KSS



KSS EC Type Cable Marker

ECA-1 / ECA-2 Material: Made of finest soft grade, strong, durable PVC that will resist oil, grease, and other material erosion. Packing: ECA-1 1000pcs/Roll | ECA-2 500pcs/Roll. Chevron cut.




KSS Marker Strip

Material: Nylon 66 (black), 94V-2. Nylon 66 PLATE with cable tie fastening hole to accommodate marker pieces for easy identification of cable runs.

Cable Ties

KSS



KSS Nylon Cable Tie

CV Series. Material	Nylon 66, 94V-2
Color	Natural and black

Wrapping Band

KSS



KSS Spiral Wrapping Band

KS Series (KS-8 -> KS24). Color: Standard in natural.

Cable Clamps

KSS



KSS Self Adhesive Tie Mount

Material	Nylon 66, 94V-2
Color	Natural



KSS Self Adhesive Tie Mount

Material	Nylon 66, 94V-2
Color	Natural

Bushings Conduits

KSS



KSS Nylon Cable Gland

Material	Nylon 66, 94V-2
Color	Black



KSS Flexible Conduit Adapter

Material	ABS, 94HB
Color	Grey



KSS Flexible Conduit

Material	PE. Flexible body facilitate your...
----------	---

Wire Connectors

KSS



KSS Screw On Wire Connector

Material	Tough thermoplastic, 94V-2...
----------	----------------------------------

Tubes

KSS



KSS Vinyl Wire End Cap

Material: Soft PVC. Suitable for all kinds of switchboard and complicated machinery to tell different colors. Soft and flexible material can be used for different shapes of end terminals.



CIRCUIT PROTECTION

Iskra

Miniature and residual current circuit breakers, overvoltage and motor protection, enclosures and switching devices for residential, commercial and industrial installations.

15 products · 7 categories



RI71 - B

Single-pole miniature circuit breaker designed for light-duty applications, ensuring fast and reliable protection against overloads and short circuits in residential and commercial electrical systems.



RI103 - B

Three-pole miniature circuit breaker offering protection for three-phase circuits. It is ideal for small industrial setups, safeguarding against overloads and short circuits.



RI104 - B

Four-pole miniature circuit breaker built for three-phase and neutral systems. It provides comprehensive circuit protection with a focus on safety and efficiency.



RI71 - C

Single-pole miniature circuit breaker with a "C" curve, suitable for moderate inrush currents. It is ideal for devices like small motors and fluorescent lighting.



RI72 - C

Two-pole miniature circuit breaker with a "C" curve, providing reliable protection for devices with moderate startup currents in residential and commercial environments.



RI73 - C

Three-pole miniature circuit breaker designed to protect three-phase circuits with moderate inrush currents, making it suitable for light industrial use.



RI74 - C

Four-pole miniature circuit breaker, offering protection for three-phase and neutral systems. It is built for moderate inrush current applications, ensuring system safety and reliability.

Residual Current Circuit Breakers



NFI2

Two-pole residual current circuit breaker designed for efficient protection against electric shocks and leakage currents in single-phase systems. It ensures safety by promptly disconnecting faulty circuits and is ideal for residential and small...



NFI4

Four-pole residual current circuit breaker offering enhanced protection in three-phase systems. It provides reliable safety against leakage currents and electrical faults, making it suitable for industrial and large commercial applications.

Overvoltage Protection

ISKRA



ISPRO C

The ISPRO C overvoltage protection device is designed to safeguard electrical systems from transient surges caused by lightning strikes or switching operations. It offers reliable protection for both residential and industrial installations,...



PV ISPRO C

The PV ISPRO C is specifically engineered for photovoltaic systems, providing robust overvoltage protection against surges on DC circuits. It ensures optimal safety and performance of solar installations, protecting inverters and other critical...

Motor Protection Circuit Breakers

ISKRA



MS25

Reliable circuit breaker designed to protect motors from overload, short circuits, and phase loss. It is easy to adjust and ensures safe and efficient motor operation in various applications.

Enclosures

ISKRA



O-55

Durable, weather-resistant boxes designed to protect electrical components in outdoor and industrial environments. They offer reliable protection against dust, water, and other environmental factors, ensuring safety and durability.

Hour Meters

ISKRA



HK-46

Compact and reliable device used to track the operating hours of machines and equipment. It is ideal for maintenance scheduling, ensuring efficient performance and reducing downtime.



BI220

Bistable switches are switching devices with two stable states for switching of all kind of electric loads. when the switch is not initiated electrically or actuated manually, remains stable in its operating position and will change its operating...



ENCLOSURES & ACCESSORIES

Tempa Pano

Wall-mounted enclosures, cover plates and profiles, DIN rails, fan filters and replacement filters.

11 products · 5 categories

Wall Mounted Enclosures

TEMPA PANO



EKO

EKO Series wall-mounted enclosures are cost-effective solutions designed for general-purpose applications. Made from durable materials, they provide reliable protection for electrical and electronic components in residential, commercial, and light...



ETS

ETS Series wall-mounted enclosures are premium enclosures offering enhanced protection with a focus on robustness and versatility. Built to withstand harsh environments, they are ideal for industrial and demanding commercial applications.

Cover Plates

TEMPA PANO



Cover Plate

A durable panel used to cover unused openings in electrical enclosures, offering safety and a clean finish.



Cover Plate Profile

A modular profile designed to cover multiple sections of an enclosure, ensuring flexibility and a tidy appearance.

Din Rails

TEMPA PANO



MR KL

A standardized metal rail used to mount circuit breakers and industrial control equipment securely inside enclosures.

Fan Filters

TEMPA PANO



FFTPTF 1000

Fan filter ensures efficient ventilation and dust filtration for small enclosures, maintaining optimal operating conditions for electrical components.



FFTPTF 2000

Fan filter is designed for medium-sized enclosures, providing reliable airflow and preventing dust accumulation to ensure equipment longevity.



FFTPTF 3000

Fan filter offers high-performance ventilation and filtration for large enclosures, ideal for demanding environments that require enhanced cooling and protection.



FFTPTFA 1000

Designed for small enclosures, ensuring clean airflow and effective dust protection for sensitive electrical components.



FFTPTFA 2000

Provides reliable filtration for medium-sized enclosures, maintaining a dust-free environment to enhance equipment performance and lifespan.



FFTPTFA 3000

Delivers high-efficiency filtration for large enclosures, offering superior dust protection and airflow for critical electrical systems in demanding environments.



ENCLOSURES & CLIMATE CONTROL

Plastim

Modular distribution boards with grey or transparent doors, and IP54 filter fans from 30 to 125 m³/h.

8 products · 2 categories

**Filter Fan 30m³/h**

PTF1000 filter fan delivers 30 m³/h airflow, 14W power, IP54 protection, and operates from -10°C to +70°C with a noise level of 28 dB(A).

**Filter Fan 100m³/h**

PTF1500 filter fan provides 100 m³/h airflow, 26W power, IP54 protection, and operates between -10°C and +70°C with a noise level of 42 dB(A).

**Filter Fan 115m³/h**

PTF2500 filter fan delivers 115 m³/h airflow, 26W power, IP54 protection, and operates from -10°C to +70°C with a noise level of 42 dB(A).

**Filter Fan 125m³/h**

PTF2000 filter fan offers 125 m³/h airflow, 26W power, IP54 protection, and operates from -10°C to +70°C with low noise at 42 dB(A).

Distribution Boards

**Plastic Grey Door**

Durable distribution board with a robust grey plastic door, suitable for general-purpose electrical installations.

**Modular Grey Door**

A modular distribution board featuring a secure grey plastic door, ideal for versatile electrical setups.

**Plastic Transparent Door**

A distribution board with a transparent plastic door for easy visibility of internal components without compromising safety.

**Modular Transparent Door**

A modular distribution board with a transparent plastic door, offering convenient monitoring and adaptability for modern electrical systems.



EARTHING & GROUNDING

Gemini

Corrosion-resistant earth rods, rod-to-cable clamps and couplings for reliable grounding systems.

3 products · 1 categories



Earth Rod

High-quality earth rods designed for effective grounding and electrical safety. Manufactured from corrosion-resistant materials, these rods ensure long-lasting performance in various environmental conditions. Ideal for grounding systems in...



Rod to Cable Clamp

Reliable rod-to-cable clamps engineered for secure connections between earthing rods and cables. Made from durable materials to ensure electrical conductivity and corrosion resistance. Easy to install and suitable for a wide range of earthing setups.



Couplings

Precision-engineered couplings designed to extend the length of earth rods securely. Made from high-strength materials for excellent durability and resistance to environmental stress. These couplings ensure a tight fit and optimal electrical...



CABLE ACCESSORIES

4C Electric

Durable PVC terminal boxes with pre-formed cable entry points for indoor and outdoor electrical connections.

1 products · 1 categories



Terminal Boxes

High-quality terminal boxes constructed from durable PVC, offering excellent protection for electrical connections. Available in various sizes, they feature pre-formed, flexible cable entry points for easy and efficient installation. These boxes are...



LIGHTING


GLOW

Locally sourced GLOW lighting: LED bulbs, panels and strips, spotlights and downlights, track and ceiling lighting, outdoor and solar ranges, plus indoor fans.

20 products · 1 categories




LED Bulbs



LED Frames & Panels



LED Strips




Aluminium Profiles



Silicone Strip Housing



MR16 Spotlights




Complete Spotlights



Slim Downlights




Ceiling Lights




2-Line Track Lights



Ultra Slim Magnetic Track



Magnetic Track 2.4G



Decorative Lighting




Outdoor Recessed



Outdoor Landscape



Modern Outdoor Surface



Classic Outdoor Surface



High-Power Flood Lights



Solar Outdoor



Indoor Fans